



# CX-80 GREASE GRAFIT

## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

**Grease grafit** is a multipurpose grease for general lubrication under normal operating conditions and loads, formulated for lubrication of all kinds of universal applications in transport, agriculture and off road equipment, operating in wet, dusty and/or dry conditions.

- Lubrication of all kinds of bearings and joints when the temperature and loading conditions are normal.
- Pre-eminently suitable for passenger car, light truck and leisure vehicle applications.
- Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

### ADVANTAGES

**Grease grafit** is miscible with most other conventional soap greases.

- Excellent mechanical stability avoiding ejection or loss of consistency during operation.
- Excellent pumpability due to the low temperature characteristics and smooth texture.
- Very good water resistance, even in a humid environment a sufficient lubricating film will be maintained.
- **Grease grafit** does not contain lead, or other heavy metals considered harmful to human health and the environment.

It is a new high performance multipurpose lubricating grease intended for operating in a wide temperatures range within -30 and 600°C continuous temperature.

Typical Characteristics	Methods	
Colour	-	Black
Dropping Point, ° C	ASTM D-566	299
Penetration at 25 ° C after 60 cycles mmx10-1	ASTM D-217	285
NLGI grade	ISO 2137	2
Graphite content%	15	