



PRODUCT DATA SHEET

Issue on 14 April 2017

Texas Petrochemical Asia Pacific Pte Ltd

Singapore 629170

Tel: 65-6262 6538

Fax: 65-6262 6537

Website: www.texaslub.com

TEXAS SPINTEX OIL

Premium Quality Spindle Oil

DESCRIPTION

Texas Spintex Oil series are a range of low-viscosity lubricants specially formulated for the lubrication of high speed spindles. It is designed with excellent rust and oxidation protection, anti-wear properties and rust and corrosion inhibitors.

PERFORMANCE STANDARDS

- Cincinnati Milacron P62, P45

MAIN APPLICATION

- Hydraulic System which required low viscosity and anti-wear lubricants.
- Industrial Circulating Systems.
- High speed spindles / bearings of spinner and twister.

BENEFITS

- Premium anti-wear, rust and oxidation additives protecting bearing surfaces against wear.
- Effective rust and corrosion inhibitors protect components under wet and humid operating condition and provide excellent resistance to thickening and degradation of oil in service.
- Maximizes equipment life and reduce maintenance cost.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability

TYPICAL PROPERTIES

ISO VG	10	15	22
Density, kg/Litre @ 15°C	0.835	0.840	0.850
Appearance	Clear	Clear	Clear
Kinematic Viscosity, mm ² /s @ 40°C	16	18	19
Kinematic Viscosity, mm ² /s @ 100°C	3.7	4.0	4.2
Pour Point, °C	-30	-30	-30
Flash Point COC, °C	190	200	210

Typical physical and chemical characteristics do not constitute as specifications. Texas Petrochemical reserves the right to amend and change the information herein without notification as a result of continual product research and development.