

FOOD GRADE LUBRICATING GREASE FOR EXTREME CONDITIONS

Caxtreme FG is a food-grade lubricating grease with excellent adhesion and based on synthetic base fluids. The grease is exceptionally water resistant, suitable for a wide range of applications, endures heavy workloads and high temperatures. Resistant against solvents, acids, etc. Mechanically stable and does not turn rancid. The synthetic base oil is developed to fulfil high demands of purity/cleanliness and differing/varying temperatures. Caxtreme FG endures high pressures and constant flushing by water without losing its lubricating properties. Perfect for chains, guides, etc.

Caxtreme FG 45 is developed for use in low temperature applications as well as where high speed is encountered.

Caxtreme FG 150 is for general lubrication of bearings, chains, guides and bushings.

Caxtreme FG 400 can be used where a higher base oil viscosity is desirable, i.e. in pellet mills.

Characteristics

Waterproof
Endures heavy workloads
Powerful adhesion
Wide range of uses

Applications

Rolling bearings
Chassis
Bushings
Food-processing industry
etc.

Technical data

NLGI grade	-	2	2	2
		Caxtreme FG 45	Caxtreme FG 150	Caxtreme FG 400
Colour	-	Beige/Brown	Beige/Brown	Beige/Brown
Base oil	-	Synthetic	Synthetic	Synthetic
Base oil viscosity at 40°C mm ² /s	ISO 3104	45	150	400
Thickener	-	Calcium sulfonate complex	Calcium sulfonate complex	Calcium sulfonate complex
Dropping Point, °C	ISO 2176	>250	>250	>250
4-ball, EP test, weld load, N	DIN 51350:4	7200	7400	7600
Application temperature range °C		-40 to >+260	-35 to >+260	-20 to >+260
Product code	-	1260	1230	1250

The product is H1 registered: Ins No 1795853

SDS – Safety Data Sheet

Available from www.cargo-oil.se or by phone +46 31-443311



Standard packages

- 18 kg pail
- 50 kg drum
- 180 kg drum
- 400 gram cartridge
- 400 g LubeShuttle® cartridge

