

BLUESIL™ FLD 47V100, 47V350 & 47V1 000

Medium Viscosity Di-Methyl Fluids

Description **BLUESIL™ FLD 47V - Medium Viscosity** products are 100% active dimethylpolysiloxanes. These silicone fluids are linear polymers characterized by low surface tension and excellent thermal stability. **BLUESIL™ FLD 47V** products are available in a complete range of viscosities between 5 and 1,000,000 cst., extending their usage to a wide variety of industrial applications.

Applications

- Mold release and anti-adherence agents
- Hydraulic, heat transfer and dielectric fluids
- Lubricants
- Antifoams
- Additives for paints and coatings
- Additives for maintenance products

Features

- Excellent high and low temperature resistance
- Excellent resistance to oxidation and hydrolysis
- Excellent resistance to atmospheric agents: oxygen, ozone, moisture, UV light
- Chemically resistant and non-corrosive
- High compressibility
- Small change in viscosity due to temperature in comparison to non-silicone oils
- Good dielectric properties
- Low surface tension
- Low freezing point

Typical Properties

	<u>47V100</u>	<u>47V350</u>	<u>47V1 000</u>
• Type	----- 100% Active Dimethylpolysiloxanes -----		
• Appearance	----- Clear, colorless liquids -----		
• Viscosity, 25°C, (77°F), cst	100	350	1000
• Specific gravity, 25°C (77°F)	0.965	0.969	0.973
• Flash point, °C, (°F), Open Cup	----- >300 (572) -----		
• Freeze point, °C, (°F)	-55 (-67)	-50 (-58)	-50 (-58)
• Refractive index, 25°C, (77°F)	1.403	1.403	1.404
• Surface tension, 25°C, (77°F), Dynes/cm	20.9	21.1	21.1
• Vapor pressure, 200°C, (392°F) mm Hg	----- 1x10 ⁻² -----		

Please note: The typical properties listed in this bulletin are not intended for use in preparing specifications for any particular application of BLUESIL™ silicone materials. Please contact our Technical Service Department for assistance in writing specifications.

FDA Status **BLUESIL™ FLD 47V Medium Viscosity** can be used in non-standardized foods (other than milk) in amounts up to ten parts per million under the Federal Food, Drug and Cosmetic Act. Any limitations on use in standardized foods should be observed.

BLUESIL™ FLD 47V Medium Viscosity may be used in the manufacture of food packaging materials, such as paper and paperboard, adhesives, and animal glues, subject to appropriate limitations on extractables (see FDA Regulations 21 CFR 173.340, 175.105, 175.300, 176.170, 176.210, 177.1210, and 178.3120).

Storage and shelf life **BLUESIL™ FLD 47V Medium Viscosity** products when stored in the original, unopened container at room temperatures (5-40°C), have practically unlimited shelf life.

BLUESIL™ FLD 47V100, 47V350 & 47V1 000

Safety

Please read the container labels for **BLUESIL™ FLD 47V Medium Viscosity** products or consult the Material Safety Data Sheet (MSDS) before handling for safe use, physical and health hazard information. The MSDS is not included with the product packaging, but can be obtained by contacting Bluestar Silicones at 866-474-6342 or consult your Bluestar Silicones representative.

Packaging

BLUESIL™ FLD 47V Medium Viscosity products are supplied in 200 kg and 1000 kg containers. Certificate of analysis for each lot purchased is available on request.

BLUESIL™ is a trademark of Bluestar Silicones

 EUROPE	 NORTH AMERICA	 LATIN AMERICA	 ASIA PACIFIC
<p><i>Bluestar Silicones France</i> 21 Avenue Georges Pompidou F69486 Lyon Cedex 03 FRANCE Tel. (33) 4 72 13 19 00 Fax (33) 4 72 13 19 88</p>	<p><i>Bluestar Silicones USA</i> Two Tower Center Boulevard Suite 1601 East Brunswick, NJ 08816-1100 United States Tel. (1) 732 227 2060 Fax (1) 732 249 7000</p>	<p><i>Bluestar Silicones Brazil Ltda.</i> Av. Maria Coelho Aguiar, 215 Bloco G - 1º Andar 05804-902 - São Paulo - SP - Brazil Tel. (55) 11 3747 7887 Fax (55) 11 3741 7718</p>	<p><i>Bluestar Silicones Hong Kong</i> Trading Co. Ltd. 29th Floor, 88 Hing Fat Street Causeway Bay Hong Kong Tel. (852) 3106 8200 Fax (852) 2979 0241</p>

Warning to users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards to infringement of or prejudice to third party rights through the use of our products. **BLUESTAR SILICONES** warrants that its products comply with its sales specifications. This information must not be used as a substitute for necessary prior tests, which ensure that a product is suitable for a given use. Determination of the suitability of product for the uses and applications contemplated by user and others shall be the sole responsibility of user. Users are responsible for ensuring compliance with local legislation and for obtaining necessary certifications and authorizations. Users are requested to ensure that they are in possession of the latest version of this document; please contact **BLUESTAR SILICONES** for the latest version and any additional information.